

STANLEY

RS25 RAIL SAW



FEATURES:

- Ergonomically-designed Long Saw Arm is standard with the RS25 and allows the operator full use of the tool in a standing position, reducing fatigue and the risk of back injury.
- Full Upright Assist Handle (over guard) is adjustable to accommodate operator preference and collapses for transport and storage of the saw.
- Indexable Swivel on the clamp arm and saw allows cutting on both sides of the rail, eliminating the need to disconnect from and reconnect to the saw clamp.
- Available in both 14" and 16" models to match application and customer needs.



SPECIFICATIONS

RS25	
Capacity (Cut Length)	12,15, & 20 in.
	30, 38, & 51 cm
Saw Weight	32 / 33 lbs.
	14.5 / 15 kg
Clamp Weight	22 lbs.
	9.9 kg
Total Weight	55 / 56 lbs.
	24.4 / 25 kg
Length	36 in.
	92 cm
Width	11 in.
	28 cm
Pressure	2000 psi
	140 bar
Flow Range	8 - 10 gpm
	30 - 38 lpm
RPM	3600 (16 in. wheel),
	4500 (14 in. wheel)
Porting	-8 SAE O-ring
Depth	18 in.
	46 cm
Connector	HTMA Flush Faced Coupler

**CUT THROUGH RAIL
FAST WITHOUT PUTTING
STRESS ON YOUR BACK -
THE POWER OF
HYDRAULICS**

RS25 RAIL SAW

STANLEY®

MODEL	PART NO.	DESCRIPTION
RS25	RS25103	Rail Saw Ce 16" Capacity
	RS25103B	Rail Saw Ce 16" Capacity - Aero Quip
	RS25113	Rail Saw Ce 14" Capacity

ACCESSORIES

ITEM NO.	DESCRIPTION
29745	Railsaw Blade - 16 in. Norton Norzone III Fastcut
22439	Railsaw Blade - 16 in. Norton AT-36
30974	Railsaw Blade - 14 in. Norton Norzone III Fastcut

WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.